



Display-Series Two-Way Base Station Owner's Manual

Go Beyond Normal Limits...
RITRON[®]
WIRELESS SOLUTIONS

**RUGGED, PROFESSIONAL TWO-WAY BASE RADIOS
ALWAYS THERE...ALWAYS READY...ALWAYS ON!** SM



- Up to 10 Channel Capability
- 12 VDC or Wall Outlet 120 VAC Operation
- NOAA Weather Channel Feature (VHF only)
- Emergency Weather Alert Feature (VHF only)
- Easy-to-Hear High Audio Output
- Call Tone
- Built-in Quiet Call[®] and Digital Quiet Call[®] Interference Eliminator
- "Z" Button - Programmable Soft Key
- 2-Tone Encode/Decode
- DTMF ANI Encoding
- Channel Scan
- 2 Watts of Power

NEW!
Expanded
Frequency List

ACCESSORIES



JBSK-12
12-Volt Adapter Kit



RHD-6X
Behind-the-ear



RHD-8X
Single Earbud



RAM-1545
Magnet-mounted
Dual-band Antenna



RSP-5
5-Watt External Speaker



RM-7
Hand Microphone

OPTIONAL/ REPLACEMENT ACCESSORIES:

AFB-1545 ... Molded Flex, Dual-band Replacement Antenna
RAM-1545 .. Magnet-mounted, Dual-band Antenna w/ BNC

RPS-1A..... Replacement 110 VAC Power Supply
CCL-M 12 VDC, Cigarette Lighter Adaptor
JBSK-12 12 VDC, Adaptor Kit

REP-2 Low Profile Earphone
RHD-1X Single Ear Headset
RHD-4X Dual Ear Headset
RHD-5X Lightweight Over-the-ear Earset /w In-line PTT
RHD-6X Lightweight Behind-the-head Earset w/ In-line PTT
RHD-8X Lightweight Earbud w/mic and In-line PTT

RSM-3X Remote Speaker Microphone
RM-7 Hand Microphone & Hang-up Bracket

RSP-5 External Speaker w/5 Watt Audio Capability
JBS-MMK... Mobile Mounting Kit
(Does not include screws to mount bracket to wall or vehicle)

HiTechWireless

Phone: 888.511.5162

Fax: 866.341.3315

Email: Sales@hitechwireless.com

www.HiTechWireless.com